

TECHNICAL DATA SHEET



SAE 20W-50 MOTORCYCLE OIL

PRODUCT # 10700

TEST	ASTM	TYPICAL
API Gravity	D-1298	29.3
Specific Gravity @ 60°F	D-1298	.8800
Density @ 60°F LBS/US Gal	D-1298	7.328
Viscosity @ 40°C, cSt	D-445	175
Viscosity @ 100°C, cSt	D-445	20
Viscosity Index	D-2270	133
Color		Light Brown
Flash Point, COC °F	D-92	450

Lucas SAE 20W-50 High Performance Motorcycle Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

Lucas SAE 20W-50 High Performance Motorcycle Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

The exclusive additive package in Lucas SAE 20W-50 High Performance Motorcycle Oil allows for extended drain intervals.

Lucas SAE 20W-50 High Performance Motorcycle Oil far exceeds all OEM specifications.

Formulated to meet ALL motorcycles that call for a SAE 20W-50 motor oil.

Meets or exceeds: API SG/SF/CC/CD • JASO MA • ACEA A3