

TECHNICAL DATA SHEET



SAE 50 wt. MOTORCYCLE OIL

PRODUCT # 10712

TEST

ASTM

TYPICAL

API Gravity	D-1298	28.7
Specific Gravity @ 60°F	D-1298	.8833
Density @ 60°F LBS/US Gal	D-1298	7.355
Viscosity @ 40°C, cSt	D-445	185
Viscosity @ 100°C, cSt	D-445	20
Viscosity Index	D-2270	125
Color		Light Brown
Flash Point, COC °F	D-92	460

Lucas SAE 50 wt. High Performance Motorcycle Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

Lucas SAE 50 wt. High Performance Motorcycle Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

The exclusive additive package in Lucas SAE 50 wt. High Performance Motorcycle Oil allows for extended drain intervals.

Lucas SAE 50 wt. High Performance Motorcycle Oil far exceeds all OEM specifications.

Formulated to meet ALL motorcycles that call for a SAE 50 wt. motor oil.

Meets or exceeds: API SG/SF/CC/CD • JASO MA • ACEA A3